



## ALLOY 6060 : 5 METRE LENGTHS



| SECTION | EX STOCK | SIZE mm |       |      | RADII mm | KILO / METRE | PERIMETER mm |
|---------|----------|---------|-------|------|----------|--------------|--------------|
|         |          | A       | B     | T    | I/E      |              |              |
| 60048   | ✓        | 12.0    | 12.0  | 1.5  |          | 0.091        | 48           |
| 60041   | *        | 12.0    | 12.0  | 1.6  | 0.30(E)  | 0.097        | 48           |
|         | *        | 12.0    | 12.0  | 3.0  |          | 0.170        | 48           |
| 90025   | ✓        | 16.0    | 16.0  | 1.6  |          | 0.132        | 64           |
| 30233   | *        | 19.0    | 19.0  | 1.5  |          | 0.148        | 76           |
| 60091   | *        | 20.0    | 20.0  | 1.4  | 0.20(E)  | 0.146        | 80           |
| 10160   | ✓        | 20.0    | 20.0  | 1.6  |          | 0.166        | 80           |
| 30892   | ✓        | 20.0    | 20.0  | 3.0  |          | 0.301        | 80           |
| 60008   | *        | 25.0    | 25.0  | 1.4  |          | 0.184        | 100          |
| 10159   | ✓        | 25.0    | 25.0  | 1.6  |          | 0.210        | 100          |
| 30079   | ✓        | 25.0    | 25.0  | 3.0  |          | 0.382        | 99           |
|         | *        | 25.0    | 25.0  | 5.0  |          | 0.610        | 100          |
| 30884   | *        | 30.0    | 30.0  | 2.0  |          | 0.314        | 119          |
| 30249   | ✓        | 30.0    | 30.0  | 3.0  |          | 0.463        | 120          |
| 90194   | *        | 30.0    | 30.0  | 5.0  |          | 0.745        | 120          |
|         | *        | 30.0    | 30.0  | 6.0  |          | 0.878        | 120          |
| 60005   | *        | 32.0    | 32.0  | 1.6  |          | 0.271        | 128          |
| 60006   | ✓        | 32.0    | 32.0  | 3.0  |          | 0.496        | 128          |
| 60045   | *        | 40.0    | 40.0  | 1.4  | 0.30(E)  | 0.298        | 159          |
| 30893   | ✓        | 40.0    | 40.0  | 1.6  |          | 0.304        | 160          |
| 60079   | *        | 40.0    | 40.0  | 2.0  | 0.50     | 0.422        | 159          |
| 30080   | ✓        | 40.0    | 40.0  | 3.0  |          | 0.626        | 159          |
| 30415   | ✓        | 40.0    | 40.0  | 4.5  |          | 0.921        | 160          |
| 60144   | ✓        | 40.0    | 40.0  | 6.0  | 0.20(E)  | 1.203        | 160          |
| 60067   | ✓        | 50.0    | 50.0  | 1.6  |          | 0.427        | 200          |
| 30232   | ✓#       | 50.0    | 50.0  | 3.0  |          | 0.789        | 200          |
| 30082   | ✓#       | 50.0    | 50.0  | 4.5  | 1.00 INT | 1.165        | 200          |
| 30081   | ✓        | 50.0    | 50.0  | 6.0  |          | 1.528        | 199          |
| 90236   | ✓        | 60.0    | 60.0  | 3.0  |          | 0.951        | 240          |
|         | *        | 60.0    | 60.0  | 6.0  |          | 1.854        | 240          |
| 30629   | ✓        | 65.0    | 65.0  | 6.0  | 0.20 (E) | 2.016        | 259          |
| 60218   | ✓        | 75.0    | 75.0  | 3.0  |          | 1.195        | 300          |
| 30742   | ✓        | 75.0    | 75.0  | 4.5  | 0.30 (E) | 1.774        | 300          |
| 30336   | ✓        | 75.0    | 75.0  | 6.0  |          | 2.341        | 300          |
|         | *        | 76.2    | 76.2  | 3.0  |          | 1.210        | 304          |
|         | *        | 76.2    | 76.2  | 9.0  |          | 3.485        | 304          |
| 60168   | *        | 100.0   | 100.0 | 3.0  |          | 1.601        | 399          |
| 60153   | ✓        | 100.0   | 100.0 | 6.0  |          | 3.154        | 399          |
| 20001   | ✓        | 100.0   | 100.0 | 10.0 | 5.00 (E) | 5.134        | 398          |

A = Width B = Height T = Thickness I = Internal Radii R = External Radii

\* Mill runs only, please ask regarding the availability of these # Other stock lengths available in this size.